According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® STANDARD ULTRA HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Hardener

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : HUNTSMAN ADVANCED MATERIALS (UK) LIMITED

Address : Ickleton Road, Duxford, Cambridgeshire

CB22 4XQ United Kingdom

Telephone : +41 61 299 20 41

E-mail address of person responsible for the SDS

nail address of person : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: +91 22 42 87 5333

Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Hazard pictograms







Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/

doctor.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved

facility in accordance with local, regional, national

and international regulations.

Hazardous components which must be listed on the label:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine Amines, polyethylenepoly-, tetraethylenepentamine fraction Amines, polyethylenepoly-, triethylenetetramine fraction

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name		Classification	Concent
	EC-No.		ration

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

	Index-No. Registration number		(% w/w)
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction	-	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 50 - < 70
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine	68154-62-1 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 30 - < 50
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7 292-587-7	Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8 292-588-2	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 0.25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralise with acid.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

Advice on common storage : Do not store near acids.

Recommended storage

temperature

: 2 - 40 °C

Further information on

storage stability

: Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
Amines, polyethylenepoly-, tetraethylenepentamin e fraction	Workers	Inhalation	Long-term systemic effects	0.82 mg/m3
	Workers	Dermal	Long-term local effects	0.25 mg/cm2
	Consumers	Inhalation	Long-term systemic effects	0.14 mg/m3
	Consumers	Dermal	Long-term local effects	0.021 mg/cm2
	Consumers	Oral	Long-term systemic effects	0.21 mg/kg bw/day
Amines, polyethylenepoly-, triethylenetetramine fraction	Workers	Inhalation	Long-term systemic effects	0.54 mg/m3
	Consumers	Inhalation	Long-term systemic effects	0.096 mg/m3
	Consumers	Oral	Long-term systemic effects	14 mg/kg bw/day

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
Amines, polyethylenepoly-,	Fresh water	0.01 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

tetraethylenepentamine fraction			
·	Remarks:Assessment Factors	<u> </u>	
	Marine water	0.001 mg/l	
	Remarks: Assessment Factors		
	Freshwater - intermittent	0.068 mg/l	
	Remarks: Assessment Factors	•	
	Sewage treatment plant	4.6 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	3.198 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method		
	Marine sediment	0.32 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method		
	Soil	2.5 mg/kg dry weight (d.w.)	
	Remarks: Assessment Factors		
Amines, polyethylenepoly-, triethylenetetramine fraction	Fresh water	0.027 mg/l	
-	Marine water	0.003 mg/l	
	Sewage treatment plant	0.13 mg/l	
	Fresh water sediment	8.572 mg/kg dry weight (d.w.)	
	Marine sediment	0.857 mg/kg dry weight (d.w.)	
	Soil	1.25 mg/kg dry weight (d.w.)	

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any

indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special

workplace conditions (mechanical strain, duration of contact).

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

EN 374 derived from it.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates and ammonia/amines type (K-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : yellow

Odour : No data is available on the product itself.

Odour Threshold : No data is available on the product itself.

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Flash point : > 150 °C

Method: Pensky-Martens closed cup

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

pH : 11

Concentration: 500 g/l

Viscosity

Viscosity, dynamic : 25,000 - 30,000 mPa.s (25 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Density : 0.97 g/cm3 (25 °C)

Relative density : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Acute oral toxicity : LD50 (Rat, male): 3,221 mg/kg

Method: Calculation method

Assessment: The component/mixture is minimally toxic after

single ingestion.

Acute dermal toxicity : LD50 (Rabbit, male and female): 1,260 mg/kg

Method: OECD Test Guideline 402

Amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, male and female): 1,716.2 mg/kg

Method: OECD Test Guideline 401

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute dermal toxicity : LD50 (Rabbit, male and female): 1,465.4 mg/kg

Method: OECD Test Guideline 402

Assessment: The component/mixture is moderately toxic after

single contact with skin.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Mild skin irritation

GLP : yes

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : human skin

Assessment : May cause eye and skin irritation.

Method : OECD Test Guideline 431

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Result : May cause eye and skin irritation.

Species : human skin Assessment : Irritant

Method : OECD Test Guideline 439

Result : Irritating to skin.

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : Irritating to skin.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Species : reconstructed human epidermis (RhE)

Assessment : Causes burns.

Method : OECD Test Guideline 435

Result : Corrosive after 3 minutes to 1 hour of exposure

GLP : yes

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : reconstructed human epidermis (RhE)

Assessment : Causes burns.

Method : OECD Test Guideline 435

Result : Corrosive after 3 minutes to 1 hour of exposure

Species : Rabbit
Assessment : Causes burns.

Method : OECD Test Guideline 404

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Species : Rabbit Assessment : Corrosive

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

GLP : yes

Remarks : May cause irreversible eye damage.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Corrosive

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : Irritating to eyes.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Assessment : Risk of serious damage to eyes. Result : Risk of serious damage to eyes.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rabbit

Assessment : Risk of serious damage to eyes.

Method : OECD Test Guideline 405

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1A.

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : May cause sensitisation by skin contact.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Assessment : May cause sensitisation by skin contact.
Result : May cause sensitisation by skin contact.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Exposure routes : Skin

Species : Guinea pig

Assessment : Probability or evidence of skin sensitisation in humans

Method : OECD Test Guideline 406

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: positive

Test Type: gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Test Type: Micronucleus test
Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Dose: 185/370/600 mg/kg

Method: OECD Test Guideline 474

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella tryphimurium and E. coli

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Test Type: Micronucleus test Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Method: OECD Test Guideline 487

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Dose: 0 - 600 mg/kg

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Mouse, male Application Route : Dermal

NOAEL : >= 50 mg/kg bw/day
Method : OECD Test Guideline 451

Result : negative

Species : Mouse, male
Application Route : Dermal
Exposure time : 104 weeks

NOAEL : >= 20 mg/kg bw/day
Method : OECD Test Guideline 451

Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Effects on foetal : Test Type: Pre-natal development : Species: Rabbit, female

Application Route: Dermal Dose: 5/50/125 mg/kg bw/d Duration of Single Treatment: 13 d

General Toxicity Maternal: NOAEL: 50 mg/kg body weight Developmental Toxicity: NOAEL: >= 125 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Remarks: Information given is based on data obtained from

similar substances.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 75/325/750 mg/kg bw/d Duration of Single Treatment: 10 d

General Toxicity Maternal: NOAEL: >= 750 mg/kg body weight Developmental Toxicity: NOAEL: >= 750 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Remarks: Information given is based on data obtained from

similar substances.

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 200/400/800 mg/kg bw(d Duration of Single Treatment: 14 d

General Toxicity Maternal: NOEL: 200 mg/kg body weight Developmental Toxicity: NOAEL: >= 400 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Remarks: Information given is based on data obtained from

similar substances.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on foetal development

Test Type: Pre-natal

Species: Rat

Application Route: Oral

Dose: 75/325/750 mg/kg bw/day Duration of Single Treatment: 10 d

General Toxicity Maternal: NOAEL: >= 750 mg/kg body weight Developmental Toxicity: NOAEL: >= 750 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit

Application Route: Dermal Dose: 5/50/125 mg/kg bw/day Duration of Single Treatment: 13 d

General Toxicity Maternal: NOAEL: 50 mg/kg body weight Developmental Toxicity: NOAEL: >= 125 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Repeated dose toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rat, male and female

NOAEL : 1000 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks
Number of exposures : 7 d

Method : Subacute toxicity

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Species : Rat, male and female

NOAEL : 350 mg/kg/d

Application Route : Oral Exposure time : 28 d

Dose : 100/350/1200 mg/kg bw/day Method : OECD Test Guideline 407

Target Organs : Lungs

Remarks : Information given is based on data obtained from similar

substances.

Species : Rat, female
NOAEL : 50 mg/kg
Application Route : Oral
Exposure time : 90 d

Dose : 50/175/600 mg/kg bw/d
Method : OECD Test Guideline 408

Target Organs : Lungs

Remarks : Information given is based on data obtained from similar

substances.

Species : Dog, male and female

NOAEL : 125 mg/kg

Application Route : Oral Exposure time : 28 d Target Organs : Lungs

Remarks : Information given is based on data obtained from similar

substances.

Species : Rat, male and female

NOAEL : 350 mg/kg
Application Route : Oral
Exposure time : 4 weeks
Number of exposures : daily

Dose : 100/350/1200 mg/kg bw/d Method : OECD Test Guideline 408

Remarks : Information given is based on data obtained from similar

substances.

Species : Rat, male and female NOAEL : 600 - 3000 ppm
Application Route : oral (drinking water)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Exposure time : 92 days

Dose : 120/600/3000 ppm

Method : OECD Test Guideline 408

Remarks : Information given is based on data obtained from similar

substances.

Species : Mouse, male and female

NOAEL : 600 ppm

Application Route : oral (drinking water)

Exposure time : 92 days

Dose : 120/600/3000 ppm

Method : OECD Test Guideline 408

Remarks : Information given is based on data obtained from similar

substances.

Species : Rabbit, male and female

NOEL : >= 200 mg/kg
Application Route : Dermal
Exposure time : 20 days 6 h
Number of exposures : 5 days/week

Dose : 50/100/200 mg/kg bw/day
Method : OECD Test Guideline 410

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rat, male and female

NOAEL : 350 mg/kg
Application Route : Oral
Exposure time : 28 d
Number of exposures : 7 d

Dose : 100/350/1000 mg/kg bw/day Method : OECD Test Guideline 407

Target Organs : Lungs

Remarks : Information given is based on data obtained from similar

substances.

Species : Dog, male and female

NOAEL : 125 mg/kg Application Route : Oral Target Organs : Lungs

Remarks : Information given is based on data obtained from similar

substances.

Species : Dog, male and female

NOAEL : 50 mg/kg Application Route : Oral

Method : Subchronic toxicity

Remarks : Information given is based on data obtained from similar

substances.

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : Oral
Exposure time : 26 weeks

Dose : 50/175/600 mg/kg bw/day

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Method : OECD Test Guideline 408

Target Organs : Lungs

Remarks : Information given is based on data obtained from similar

substances.

Species : Mouse, male and female NOAEL : 92 mg/kg, 600 ppm

Application Route : Oral

Exposure time : 120/600/3000 ppm
Method : OECD Test Guideline 408

Remarks : Information given is based on data obtained from similar

substances.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components

considered to have endocrine disrupting properties for human

health according to UK REACH Article 57(f),

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 5.18 mg/l

Exposure time: 48 h

Test Type: static test
Test substance: Fresh water

Method: OECD Test Guideline 202

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 2.43 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): 421 mg/l

Exposure time: 3 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 209

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 420 mg/l

End point: mortality
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.1.

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 24.1 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test

Test substance: Fresh water

Method: Tested according to Annex V of Directive

67/548/EEC.

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 6.8 mg/l

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 0.5 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 97.3 mg/l

Exposure time: 2 h Test Type: static test

Test substance: Fresh water

NOEC: 500 mg/l Exposure time: 28 d

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Method: OECD Test Guideline 216

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC10: 1.9 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Fresh water Method: OECD Test Guideline 202

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to soil dwelling

organisms

NOEC: 125 mg/kg Exposure time: 55 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 222

Amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 570 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.1.

LC50 (Leuciscus idus (Golden orfe)): 200 - 500 mg/l

Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 330 mg/l

End point: mortality Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: EPA OTS 797.1400

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 31.1 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test

Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l

Exposure time: 72 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

EC10 (Selenastrum capricornutum (green algae)): 1.34 mg/l

Exposure time: 72 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Bacteria): >= 100 mg/l

Exposure time: 28 d

Method: OECD Test Guideline 216

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

EC50 (Bacteria): > 100 mg/l

Exposure time: 28 h

Method: OECD Test Guideline 216

EC50 (Bacteria): 15.7 mg/l Exposure time: 2 h Test Type: static test

Test substance: Fresh water

NOEC (Bacteria): 1.3 mg/l Exposure time: 2 h Test Type: static test Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC10: 1.9 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to soil dwelling

organisms

NOEC: ca. 62.5 mg/kg Exposure time: 56 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 222

EC50: > 1,000 mg/kg Exposure time: 56 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 222

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge

Result: Not inherently biodegradable.

Biodegradation: 17 % Exposure time: 84 d

Method: OECD Test Guideline 302 A

Test substance: Fresh water

Test Type: aerobic Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 162 d

Method: OECD Test Guideline 301D

Test substance: Fresh water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Amines, polyethylenepoly-, triethylenetetramine fraction:

Biodegradability : Inoculum: activated sludge

Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 162 d

Method: OECD Test Guideline 301D

Test substance: Fresh water

Test Type: aerobic

Inoculum: activated sludge

Result: Not inherently biodegradable.

Biodegradation: 20 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 84 d

Method: OECD Test Guideline 302A

Test substance: Fresh water

12.3 Bioaccumulative potential

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Partition coefficient: n-

octanol/water

: log Pow: -2.6 (20 °C)

Amines, polyethylenepoly-, triethylenetetramine fraction:

Partition coefficient: n- : log Pow: -2.08 - 2.90 (20 °C)

octanol/water Method: QSAR

12.4 Mobility in soil

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Distribution among : Koc: 3.2 - 3.7

environmental compartments Method: OECD Test Guideline 106

Amines, polyethylenepoly-, triethylenetetramine fraction:

Distribution among : Koc: 3162.28, log Koc: 3.5

environmental compartments Method: OECD Test Guideline 106

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(POLYAMIDE RESIN)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 9 **RID** : 9

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

IMDG : 9 **IATA** : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III Labels : 9

EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

964

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered: Number on list 3

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

This product does not contain substances of very high concern.

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

Further information

Classification of the mixture: Classification procedure:

Eye Dam. 1 H318 Based on product data or assessment

Skin Sens. 1 H317 Calculation method Aquatic Chronic 2 H411 Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® STANDARD ULTRA HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 2.6
 18.10.2024
 400001021218
 Date of first issue: 20.07.2018

Print Date 20.01.2025

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.